



PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Reference: SG351TWA002 /

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	296
Continuous power three phase (KW)	283.3
Maximum power three phase (KVA)	370
Continuous power three phase (KVA)	354.13
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	VOLVO TAD1342GE, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	12780
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	36
Cooling	Water
Alternator	Mecc Alte ECO38-3LN/4, brushless
Poles	4
Fuel tank capacity (L)	636
Consumption (L/h)	54.4 at 75% of the load / 71.1 at 100% of the load

Running time (h)	11.7 at 75% of the load / 8.9 at 100% of the load
Length (mm)	3300
Width (mm)	1460
Height (mm)	1965
Dry weight (Kg)	3160
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Volvo