

PRAMAC GSW45P COFANATO CON QUADRO COMANDO MANUALE

Reference: SU450TPAR00 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	38.4
Continuous power three phase (KW)	36.59
Maximum power three phase (KVA)	48
Continuous power three phase (KVA)	45.74
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 63A 3P+N+T - 1 x 400V 32A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	PERKINS 1103A-33TG1, turbocharged
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	3300
Number cylinders	3
Cylinders' position	In line
Oil capacity (L)	7.9
Cooling	Water
Alternator	Mecc Alte ECO/P32-3S/4, brushless
Poles	4
Fuel tank capacity (L)	68
Consumption (L/h)	8.2 at 75% of the load / 10.7 at 100% of the load

Running time (h)	8.3 at 75% of the load / 6.4 at 100% of the load
Acoustic power	95 dB(A)
Acoustic pressure	66 dB(A) at 7 m
Length (mm)	2000
Width (mm)	920
Height (mm)	1310
Dry weight (Kg)	958
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Perkins