



## LIGHTING TOWER 4X320

Reference: 4X320TF

### LIGHTING TOWER 4X320

The 4X320 Lighting Tower is a hydraulically-lifted lighting tower equipped with 4 floodlights, each delivering 320W of light output.

The 4X320 Lighting Tower is equipped with a galvanized steel lifting tower that can extend up to a maximum height of 8.5 meters, including 4 stabilizing feet to secure the lighting tower once opened.

The 4X320 Lighting Tower has an input plug and a 16A 230V output socket, allowing it to be combined with other units.

The Lighting Tower The 4X320 is designed to be paired with a generator and can be connected in series to use a single generator for multiple lighting units.

The light tower's lenses are equipped with extremely special optics designed specifically for the civil engineering and construction sectors. This innovative design of the fully directional LED lenses ensures maximized light diffusion and reduced waste.

The 4X320 is characterized by extremely compact dimensions and a square shape that optimize and facilitate its positioning and transport on mobile vehicles. The base, with 4 adjustable and removable anti-tipping stabilizers, guarantees wind stability of 110 km/h.

#### TECHNICAL FEATURES 4X320 Light Tower

Projectors: 4 x 320W LEDs  
Illuminated Area: 5000 m<sup>2</sup>  
Total Lumens: 166200 lm  
Max Height: 8.5 m  
Lifting: Hydraulic  
Extra sockets: 1 x 16A CEE / 230 V  
Mast sections: 6  
Manual stabilizers: 4  
Lifting hooks: 4  
Max wind resistance: 110 km/h  
Fork passage guides: STD  
Transport: Stationary  
Voltage: 230V  
Frequency: 50 Hz  
Closed dimensions: 980x1180x2237 mm  
Open dimensions: 2450x2658x8500 mm  
Dry weight: 550 kg

Looking for a product with different features?[HERE](#) You can find the entire range.

## Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Starting system	Elettrico
Maximum height (m)	8.5
Type of lamps	LED
Telescopic pole	Galvanized steel
Illuminated area (m <sup>2</sup> )	5000
Total lumens (Lm)	166200
Lifting System	Hydraulic lifting system
Mast rotation	350°
Open size (mm)	2450x2658x8500
Closed size (mm)	980x1180x2237
With generator / Without generator	Without generator
Transportability	Stationary
Dry weight (Kg)	550