

PRAMAC GSW50Y COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SU440TYAX02 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	37.03
Continuous power three phase (KW)	35.18
Maximum power three phase (KVA)	46.29
Continuous power three phase (KVA)	43.97
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 63A 3P+N+T
Engine	Yanmar 4TNV98T-ZGPGE, turbocharged
Emissions Regulations	Stage 3A
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	3319
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	11.2
Cooling	Water
Alternator	Mecc Alte ECO/P32-3S/4, brushless
Poles	4
Fuel tank capacity (L)	68

Consumption (L/h)	8.3 at 75% of the load / 11.1 at 100% of the load
Running time (h)	8.2 at 75% of the load / 6.1 at 100% of the load
Acoustic power	95 dB(A)
Acoustic pressure	66 dB(A) at 7 m
Length (mm)	2000
Width (mm)	920
Height (mm)	1310
Dry weight (Kg)	839
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Yanmar