



PRAMAC LIFTER MOTORIZED MANUAL PALLET TRUCK AGILE S4 1150x525

Reference: EJ14110BT00

PRAMAC Lifter AGILE 1150x525 cm pallet truck

The **PRAMAC LIFTER AGILE S4 1150x525 electric pallet truck** is the ideal solution for moving loads up to **1200 kg** in a practical, silent and safe way. Thanks to the **electric propulsion** and the **walk-behind driving system**, it allows precise maneuvering even in tight spaces, reducing operator effort.

Equipped with **4 rear wheels** for greater stability, the AGILE S4 model offers a lifting height of **115 mm** and a turning radius of **1382 mm**, ensuring excellent maneuverability. The **1150 mm long and 150 mm wide forks ensure compatibility with most standard European pallets**.

With an **total length of 1600 mm** and an **total width of 525 mm**, this pallet truck combines compact dimensions and motorized power, making it perfect for storage operations in narrow aisles (minimum aisle 2063 mm).

Technical characteristics:

Propulsion type: Electric
Driving system: Pedestrian
Capacity: 1200 kg
Number of rear wheels: 4
Height Lifting height: 115 mm
Overall length: 1600 mm
Overall width: 525 mm
Fork width: 150 mm
Fork length: 1150 mm
Aisle width: 2063 mm
Turning radius: 1382 mm

If you are looking for another type of product for the transport and storage of goods, then you can consult our catalogue with a wide selection of products.

Technical Sheet

Drive

Electric

Operator type	Pedestrian
Load capacity (Kg)	1200
Load centre distance (mm)	600
Load axle to end forks (mm)	932
Wheel base (mm)	1192
Service weight (Kg)	92
Axle load, laden rear (Kg)	893
Axle load, laden front (Kg)	399
Axle load, unladen front (Kg)	65
Axle load, unladen rear (Kg)	27
Tyres: front wheels	GOMMA
Tyres: rear wheels	POLY
Diameter steering wheels (mm)	200
Width steering wheels (mm)	40
Diameter load rollers (mm)	82
Width load rollers (mm)	60
Quantity rear wheels	4
Rear balancing axle	No
Tread front (mm)	162
Tread rear (mm)	375
Lift height (mm)	115
Height of tiller in drive position max (mm)	1185
Height lowered (mm)	85
Overall length (mm)	1600
Length to face of forks (mm)	450
Overall width (mm)	525
Thickness fork (mm)	55
Width fork (mm)	150
Length fork (mm)	1150
Distance between fork arms (mm)	525
Ground clearance at centre of wheelbase (mm)	30
Aisle width (mm)	2063
Turning radius (mm)	1382
Travel speed laden (Km/h)	4.2
Travel speed unladen (Km/h)	5.3

Lifting speed laden (strokes)	12
Lifting speed unladen (strokes)	12
Lowering speed laden (m/s)	0.1
Lowering speed unladen (m/s)	0.02
Max gradeability laden (%)	5
Max gradeability unladen (%)	10
Service brake	Electric
Drive motor power (KW)	2x0.25
Battery voltage (V)	36
Battery capacity min (Ah)	17
Battery weight min (Kg)	3
Sound level at driver's ear	60