



PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Reference: SG501TWAR02 /

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	436.8
Continuous power three phase (KW)	403.77
Maximum power three phase (KVA)	546
Continuous power three phase (KVA)	504.71
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	VOLVO TAD1641GE, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	16120
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	48
Cooling	Water
Alternator	Mecc Alte ECO40-3S/4, brushless
Poles	4
Fuel tank capacity (L)	636
Consumption (L/h)	77.6 at 75% of the load / 104.4 at 100% of the load

Running time (h)	8.2 at 75% of the load / 6.1 at 100% of the load
Length (mm)	3500
Width (mm)	1500
Height (mm)	2120
Dry weight (Kg)	3467
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Volvo