

PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Reference: SG600TCAW00 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	53.14
Continuous power three phase (KW)	48.18
Maximum power three phase (KVA)	66.43
Continuous power three phase (KVA)	60.22
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	FPT NEF45SM1A, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	4500
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	12.8
Cooling	Water
Alternator	Mecc Alte ECO/P32-2L/4, brushless
Poles	4
Fuel tank capacity (L)	240
Consumption (L/h)	10.2 at 75% of the load / 13.7 at 100% of the load

Running time (h)	23.4 at 75% of the load / 17.5 at 100% of the load
Length (mm)	2200
Width (mm)	1000
Height (mm)	1743
Dry weight (Kg)	1123
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco