

PRAMAC GSW65I CANOPIED WITH MANUAL CONTROL PANEL

Reference: SU600TCAW00 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	53.14
Continuous power three phase (KW)	48.18
Maximum power three phase (KVA)	66.43
Continuous power three phase (KVA)	60.22
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	FPT NEF45SM1A, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	4500
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	12.8
Cooling	Water
Alternator	Mecc Alte ECO/P32-2L/4, brushless
Poles	4
Fuel tank capacity (L)	209
Consumption (L/h)	10.2 at 75% of the load / 13.7 at 100% of the load

Running time (h)	20.4 at 75% of the load / 15.3 at 100% of the load
Acoustic power	95 dB(A)
Acoustic pressure	67 dB(A) at 7 m
Length (mm)	2400
Width (mm)	1000
Height (mm)	1530
Dry weight (Kg)	1440
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco