



TECNOGEN LD 11000 TELX AVR

Reference: LD 11000 TELX

TECNOGEN LD 11000 TELX AVR

TECNOGEN LD11000TELX three-phase 8.8 kW generator with a 3000 rpm Kohler diesel engine. The TECNOGEN LD11000TELX generator is easy to use and compact, easy to handle, and easy to maintain. The TECNOGEN LD11000TELX generator is equipped with an electric start. This generator is perfect for both hobbyist and professional use, thanks to the reliable Kohler diesel engine and all its high-quality components.

Why buy an LD11000TELX generator?

First of all, they solve problems of lack of electricity during blackouts in various environments, from homes to businesses. The TECNOGEN LD11000TELX generator is also used to provide electricity on construction sites and for hobby use. Professional generators are lightweight, easy to transport, compact, and robust, simple to use, and have low operating costs. They also offer an excellent quality/price ratio.

It is possible to install lifting hooks on the TECNOGEN LD11000TELX generator set, which are very convenient for moving the generator with an overhead crane or a small crane.

Main features:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 8.8 KW

Continuous three-phase power: 8 KW

Fuel: Diesel

Voltage: 230/400V

Engine: Kohler 25LD425

Starting: Electric

Length: 990 mm

Width: 560 mm

Height: 690 mm

Weight: 160 Kg

The entire TECNOGEN range

TECNOGEN generator sets are available in both single-phase and three-phase versions. Three-phase, with power outputs from 2.3 to 21 kVA MAX, equipped with air-cooled gasoline or diesel engines, 3000 rpm, electric and/or manual recoil start. Compact, simple, and economical, they boast an excellent price/performance/size/weight ratio. Easily transportable thanks to their compact size resulting from a basic setup, they are suitable for anyone requiring an economical power source, yet assembled with top-notch components that guarantee absolute reliability. The TECNOGEN gasoline versions of the COMPACT line, thanks to the latest-generation Honda engines, meet the parameters of the 2000/14/EC noise directive.

Are you looking for a different model of current generator? Visit the section dedicated to [generators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	8.8
Continuous power three phase (KW)	8
Maximum power three phase (KVA)	11
Continuous power three phase (KVA)	10
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	KOHLER 25LD425
Emissions Regulations	Stationary Use
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	851
Number cylinders	2
Cooling	Air
Fuel tank capacity (L)	20
Consumption (L/h)	2.3 al 75% del carico
Running time (h)	8.7
Length (mm)	990
Width (mm)	560
Height (mm)	690
Dry weight (Kg)	160
Silenced	No
Super silenced	No
Voltage regulator	AVR
Engine manufacturer	Kohler