



Genmac Gruppo Elettrogeno StageV 60KVA

Reference: 04788

Genmac KING-RENT G60DSS-M5 StageV 60KVA Generator Set

The Genmac**StageV 60KVA Generator Set** is a reliable and high-performance solution for professional and industrial applications that require energy continuity and stability. This Genmac**StageV 60KVA Generator Set** offers a maximum three-phase power of 60 kVA (60 kW) and a continuous power of 48 kVA (48 kW), ensuring constant performance even under prolonged use.

Equipped with a DOOSAN D34 engine at 1500 rpm and diesel power, the Genmac**StageV 60KVA Generator Set** ensures efficiency, durability and optimized consumption. The water cooling system and electric start make it easy to use, while the AVR voltage regulator ensures stable power supply at 230/400 V and 50 Hz.

Thanks to the 150-liter tank, the Genmac**StageV 60KVA Generator Set** reaches an autonomy of up to 14 hours, making it ideal for construction sites, events or energy backup. The silenced structure with a sound pressure of only 65 dB(A) at 7 meters makes it suitable even for noise-sensitive environments.

Compact in size (2430 x 1056 x 1600 mm) and weighing 1456 kg, the Genmac**Stage V 60KVA Generator Set** represents a robust and versatile choice for those looking for a reliable three-phase diesel generator that complies with modern standards.

Technical characteristics:

Phase type: Single-phase / Three-phase
Maximum three-phase power: 60 kW
Continuous three-phase power: 48 kW
Maximum three-phase power: 60 kVA
Continuous three-phase power: 48 kVA
Fuel: Diesel
Frequency: 50 Hz
Voltage: 230/400 V
Engine: DOOSAN D34
Engine speed: 1500 rpm
Starter: Electric
Cooling: Water
Tank capacity: 150 L
Running time: 14 h
Sound pressure: 65 dB(A) at 7 m
Length: 2430 mm
Width: 1056 mm
Height: 1600 mm
Dry weight: 1456 kg
Silenced: Yes

Voltage regulator: AVR
Engine brand: Doosan

If you are looking for another product, you can consult our other catalog [ground-based generators](#).

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	60
Continuous power three phase (KW)	48
Maximum power three phase (KVA)	60
Continuous power three phase (KVA)	48
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230/400
Engine	DOOSAN D34
Engine rpm (rpm)	1500
Starting system	Elettrico
Cooling	Water
Fuel tank capacity (L)	150
Running time (h)	14 h
Acoustic pressure	65 dB(A) at 7 m
Dry weight (Kg)	1456
Silenced	Yes
Voltage regulator	AVR
Engine manufacturer	Doosan