

PRAMAC GSW80I COFANATO CON QUADRO COMANDO MANUALE

Reference: SU750TCAW00 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	65.94
Continuous power three phase (KW)	59.95
Maximum power three phase (KVA)	82.42
Continuous power three phase (KVA)	74.94
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	FPT NEF45SM2A, turbocharged
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	4500
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	12.8
Cooling	Water
Alternator	Mecc Alte ECO/P32-3L/4, brushless
Poles	4
Fuel tank capacity (L)	209
Consumption (L/h)	12.8 at 75% of the load / 17.2 at 100% of the load
Running time (h)	16.3 at 75% of the load / 12.2 at 100% of the load

Acoustic power	94 dB(A)
Acoustic pressure	65 dB(A) at 7 m
Length (mm)	2400
Width (mm)	1000
Height (mm)	1530
Dry weight (Kg)	1426
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco