

PRAMAC GSW80P COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SU800TPAV02 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	66.4
Continuous power three phase (KW)	62.4
Maximum power three phase (KVA)	83
Continuous power three phase (KVA)	78
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	PERKINS 1104A-44TG2, turbocharged
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	4400
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	8
Cooling	Water
Alternator	Mecc Alte ECO/P32-3L/4, brushless
Poles	4
Fuel tank capacity (L)	209
Consumption (L/h)	13.4 at 75% of the load / 17.9 at 100% of the load
Running time (h)	15.5 at 75% of the load / 11.7 at 100% of the load

Acoustic power	96 dB(A)
Acoustic pressure	67 dB(A) at 7 m
Length (mm)	2285
Width (mm)	920
Height (mm)	1465
Dry weight (Kg)	1144
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Perkins