



POWERMATE WX 6200 SINGLE PHASE GENERATOR 7.25 KVA AVR ELECTRIC STARTER

Reference: PR532SXBZ03

POWERMATE WX 6200 SINGLE-PHASE GENERATOR 7.25 KVA AVR

POWERMATE WX 6200 is a single-phase generator equipped with a 4-stroke gasoline engine with electric start, capable of delivering a maximum power of 7.25 KVA complete with AVR voltage regulator.

The POWERMATE WX 6200, is equipped with sturdy handles and wheels that allow easy portability; like the entire POWERMATE WX 6200 range, it is a generator set that meets a high quality standard and guarantees a high level of reliability.

The strengths of the POWERMATE WX 6200 are: the high quality of components, light weight, compactness, portability and ease of use and also modern design. The single-phase 7.25 KVA generator is equipped with a manual rope starter.

The POWERMATE WX 6200 has been specially developed for camping, caravans, homes, and hobby applications, etc., so it reflects distinctive features and convenience that allow it to be reliable and convenient in application areas.

The advantages of AVR

The automatic voltage regulator, or AVR allows the single-phase 7.25 KVA generator to deliver stable power and thus be able to connect equipment with sensitive electronics such as computers, household appliances, smartphones and tablets: the generator set is therefore ideal for use in the home, camping, hobby and leisure, but also for construction sites and craftsmen. The AVR voltage regulator and the other quality standard of the alternator with copper windings will provide you with safe and stabilized power.

Technical Features of the POWERMATE WX 6200

Phase Type: Single-Phase
Continuous Single-Phase Power: 6.63 KVA / 5.3 KW
Maximum Single-Phase Power: 7.25 KVA / 5.8 KW
VAC Voltage: 230 V
Frequency (Hz): 50
Voltage Regulator: AVR
Starting Frame: Electric
Engine: OHV 4-Stroke
Emission Standard: Stage V
RPM: 3000
Power supply: Gasoline
Fuel tank capacity: 26 l
Consumption @ 75 % load: 2.17 l/h

Autonomy @ 75 % load: 12 h
Sound pressure: 69 dB(A) @ 7m
Length: 800 mm
Width: 698 mm
Height: 620 mm
Net weight: 89 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to POWERMATE generators or other specialized brands

Pictures and data are not binding and may be subject to revisions.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	5.8
Continuous power single phase (KW)	5.3
Maximum power single phase (KVA)	7.25
Continuous power single phase (KVA)	6.63
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Elettrico
Cooling	Air
Fuel tank capacity (L)	26
Consumption (L/h)	2.16
Running time (h)	12
Acoustic pressure	69 dB(A) at 7 m
Width (mm)	698
Height (mm)	620
Dry weight (Kg)	89
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR