



PRAMAC PX3250

Reference: PK332SX1000

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.6
Continuous power single phase (KW)	2.7
Maximum power single phase (KVA)	4
Continuous power single phase (KVA)	3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	PRAMAC AP188F, naturally aspirated
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Pull starter
Engine capacity (cm ³)	389
Oil capacity (L)	1.1
Cooling	Air
Poles	2
Fuel tank capacity (L)	25.5
Consumption (L/h)	1.43 at 75% of the load / 1.92 at 100% of the load
Running time (h)	17.71 at 75% of the load / 13.28 at 100% of the load
Acoustic power	97 dB(A)

Acoustic pressure	73 dB(A) at 7 m
Length (mm)	727
Width (mm)	515
Height (mm)	670
Dry weight (Kg)	79
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	PRAMAC