



PRAMAC P11000 Generator set Single-phase 9.7KW IPP

Reference: PF113SY4000

Electric generator PRAMAC P11000 Single Phase 9.7 KW Super Silent

The PRAMAC P11000 single-phase electric generator with a 9.7 KW diesel engine at 3000 rpm. The PRAMAC P11000 electric generator features electric start. The alternator of the PRAMAC P11000 electric generator comes with a capacitor voltage regulator. The Yanmar diesel engine makes the P11000 generator very reliable as it has been built and designed using high-quality materials.

Thanks to its casing, it can be considered super silent, and with its compact dimensions, it can be easily handled and transported. The PRAMAC P11000 single-phase electric generator is suitable for outdoor use in small construction sites or for small outdoor jobs.

Technical specifications of the PRAMAC P11000 Single Phase electric generator:

Maximum Single Phase Power: 9.7 KW
Continuous Single Phase Power: 9 KW
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Engine: Yanmar 3TNV70-HGE
Start: Electric
Consumption: 3.97 Lt/h at 100% load
Length: 1400 mm
Width: 650 mm
Height: 975 mm
Weight: 325 Kg

CONTROL PANEL

Controls:

- Start key: OFF - ON - START

Instruments:

- Voltmeter

- Hour meter

- Low oil pressure light

Protections:

- Circuit breaker
- Isometer Protection (IPP)

Sockets:

2 x 2P+T CEE 230V 16A IP44

1 x 2P+T CEE 230V 32A IP44

The PRAMAC P11000 power generator is a professional diesel electric generator developed by Pramac with a diesel engine in a covered and soundproof version, ideal for residential use. With its quietness, the PRAMAC P11000 power generator is the ideal generator for use in residential areas or outside of working hours. The P11000 generator is equipped with high-quality components and complete instrumentation for use on construction sites or to cope with any blackouts.

If you are looking for an electric generator like the single-phase P11000 power generator, we recommend browsing our catalog of land-based electric generators to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	9.7
Continuous power single phase (KW)	9
Maximum power single phase (KVA)	10.8
Continuous power single phase (KVA)	10
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE
Engine	Yanmar 3TNV70-HGE, naturally aspirated
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	854
Oil capacity (L)	3.8
Cooling	Water
Poles	2

Acoustic power	96 dB(A)
Acoustic pressure	68 dB(A) at 7 m
