



PRAMAC P12000 THREE PHASE DIESEL IPP

Reference: PF113TZA00

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	9.5
Continuous power single phase (KW)	6.8
Maximum power single phase (KVA)	9.1
Continuous power single phase (KVA)	8.5
Maximum power three phase (KW)	12.6
Continuous power three phase (KW)	9.6
Maximum power three phase (KVA)	15.8
Continuous power three phase (KVA)	12
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE
Engine	Hatz 2G40, naturally aspirated
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	997
Oil capacity (L)	2.5
Cooling	Air
Poles	2

Fuel tank capacity (L)	17
Consumption (L/h)	2.74 at 75% of the load / 3.66 at 100% of the load
Running time (h)	6.20 at 75% of the load / 4.64 at 100% of the load
Acoustic power	97 dB(A)
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	1270
Width (mm)	610
Height (mm)	816
Dry weight (Kg)	275
Silenced	Yes
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Compound
Engine manufacturer	Hatz