



PRAMAC P9000 SINGLE PHASE DPP AVR

Reference: PF752SRAY03

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	7.9
Continuous power single phase (KW)	6.8
Maximum power single phase (KVA)	8.8
Continuous power single phase (KVA)	7.6
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	Lombardini 25LD330, naturally aspirated
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	654
Oil capacity (L)	1.8
Cooling	Air
Alternator	Brushless
Poles	2
Fuel tank capacity (L)	24
Consumption (L/h)	2.17 at 75% of the load / 2.90 at 100% of the load
Running time (h)	11.06 at 75% of the load / 8.25 at 100% of the load

Acoustic power	97 dB(A)
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	990
Width (mm)	602
Height (mm)	826
Dry weight (Kg)	204
Silenced	Yes
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Lombardini