



PRAMAC P9000 THREE PHASE DPP AVR

Reference: PF882TRAY03

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	4.32
Continuous power single phase (KW)	4
Maximum power single phase (KVA)	5.4
Continuous power single phase (KVA)	5
Maximum power three phase (KW)	8.5
Continuous power three phase (KW)	7.3
Maximum power three phase (KVA)	10.6
Continuous power three phase (KVA)	9.1
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	Lombardini 25LD330, naturally aspirated
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	654
Oil capacity (L)	1.8
Cooling	Air
Alternator	Brushless

Poles	2
Fuel tank capacity (L)	24
Consumption (L/h)	2.18 at 75% of the load / 2.91 at 100% of the load
Running time (h)	11.01 at 75% of the load / 8.25 at 100% of the load
Acoustic power	97 dB(A)
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	990
Width (mm)	602
Height (mm)	826
Dry weight (Kg)	207
Silenced	Yes
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Lombardini