



WFM 14000-MTHE

Reference: 09243

BOXER P Series

Generating sets with original HONDA twin-cylinder petrol engine in a sturdy semi-casing frame with power from 10 to 12 KVA, single-phase or three-phase/single-phase, 3000 rpm, air cooling, key start including battery and electrical panel with sockets and protection as standard. Can be combined with various accessories for professional use and use in the event of a blackout.

Complete with a 20-litre tank for long operating autonomy.

Not intended for outdoor use.

Noise level does not comply with Directive 2000/14/EC.

Main features:

- protective frame with semi-enveloping upper hood
- original Honda engine compliant with low CO2 emissions
- low oil level protection
- silencer
- primary Italian brand alternator
- oversized 20-litre petrol tank for long operating autonomy
- electric start with 12V battery supplied with acid
- full load test with test certificate
- user manual compliant with safety standards

The images are purely indicative.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	3.2
Maximum power single phase (KVA)	4
Maximum power three phase (KW)	9.6
Maximum power three phase (KVA)	12
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 230V 16A 3P CEE - 1 x 230V 32A 3P CEE

Engine	Honda GX690R
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	688
Number cylinders	2
Oil capacity (L)	1.9
Cooling	Air
Fuel tank capacity (L)	20
Consumption (L/h)	4.6 at 100% of the load
Running time (h)	4.34 at 100% of the load
Acoustic power	100 dB(A)
Acoustic pressure	75 dB(A) at 7 m
Length (mm)	990
Width (mm)	550
Height (mm)	670
Dry weight (Kg)	140
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	No
Engine manufacturer	Honda