



## GENSET MG 3000 I-HE GENERATOR SINGLE PHASE 3 KVA

Reference: MG 3000 I-HE

### GENSET MG 3000 I-HE GENERATOR SINGLEPHASE 3 KVA

The generator GENSET MG 3000 I-HE singlephase is equipped with a gasoline engine capable of delivering 3 KVA with voltage regulator.

The GENSET MG 3000 I-HE single-phase generator provides reliable power for home, work and recreation environments Safely powering appliances and other electronic devices solution for outdoor parties.

Generator is as easy to install and operate as it is to start and stop thanks to clear, intuitive controls (pull start) Auto shut-off for low oil level Durable frame.

GENSET MG 3000 I-HE has an all-steel construction and a large metal tank with fill indicator. The generator provides efficient and quiet operation thanks to the Honda OHV engine that allows to deliver a maximum power of 3 KVA.

#### TECHNICAL FEATURES GENSET MG 3000 I-HE

Phase Type: SinglePhase  
Maximum SinglePhase Output: 3 KVA  
Maximum SinglePhase Output: 2.4 KW  
VAC Voltage: 230 V  
Frequency (Hz): 50  
Quadro Starter: Manual with self-winding  
Motor: Honda GX 160 OHV  
Emission Standard: Stage V  
RPM: 3000  
Power supply: Gasoline  
Fuel tank capacity: 3.1 l  
Consumption @ 75 % load: 1.4 l/h  
Autonomy @ 50 % load: 2.21 h  
Sound pressure: 95 dB(A) @ 7m  
Length: 610 mm  
Width: 360 mm  
Height: 410 mm  
Net weight: 36 Kg

Looking for a generator with different characteristics? [Here](#) you can find the full range of generators GENSET or other specialized brands

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2.4
Maximum power single phase (KVA)	3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 Schuko
Engine	Honda GX160, 4 stroke, OHV
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Ignition	Recoil
Starting system	Manual
Engine capacity (cm <sup>3</sup> )	163
Number cylinders	1
Cooling	Air
Protection degree	IP23
Motor insulation class	H
Fuel tank capacity (L)	3.1
Consumption (L/h)	1.4
Running time (h)	2.21
Acoustic power	95 dB(A)
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	610
Width (mm)	360
Height (mm)	410
Dry weight (Kg)	36
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	No
Engine manufacturer	Honda