



GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

Reference: MG 8000 BS/HA

GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

GENSET MG 8000 BS/HA Single-phase generating set with Honda GX 390 OHV STAGE V engine powered by gasoline, capable of delivering a maximum power of 7 KVA complete with AVR voltage regulator.

The GENSET MG 8000 BS/HA generator set is compact and easy to use, equipped with a casing that lowers noise emissions and makes it super-silenced.

The GENSET MG 8000 BS/HA is equipped with electric start with 12 V battery and low fuel consumption, in fact it consumes only 3.3 liters/hour at 75% load.

The generator set GENSET MG 8000 BS/HA is part of the silenced series and are characterized by lower consumption and a longer life expectancy than the range powered by gasoline and equipped with soundproof cabin suitable for installation and outdoor use, and increased tank. The GENSET MG 8000 BS/HA generator set at 3000 rpm is suitable for emergency use only. It is not recommended to use it for more than 6 continuous hours and for more than 500 hours per year.

TECHNICAL FEATURES GENSET MG 8000 BS/HA

Phase Type: Single-Phase
Maximum Single-Phase Power: 7 KVA / 5.6 KW
VAC Voltage: 230 / 400 V
Frequency (Hz): 50
Quadro Starter: Manual with self-winding
Motor: Honda GX 390 OHV
Emission Standard: STAGEV
RPM: 3000
Power supply: Gasoline
Fuel tank capacity: 10.5 l
Consumption @ 75 % load: 3.3 l/h
Autonomy @ 75 % load: 3.18 h
Sound pressure: 86 dB(A)
Length: 1059 mm
Width: 670 mm
Height: 740 mm
Net weight: 138 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the full range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	5.6
Maximum power single phase (KVA)	7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A CEE - 1 x 230V 32A CEE
Engine	Honda GX390, 4 stroke, OHV
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	390
Number cylinders	1
Cooling	Air
Alternator	Synchronous
Protection degree	IP23
Motor insulation class	H
Fuel tank capacity (L)	10.5
Consumption (L/h)	3.3
Running time (h)	3.18
Acoustic power	86 dB(A)
Acoustic pressure	61 dB(A) at 7 m
Length (mm)	1059
Width (mm)	670
Height (mm)	740
Dry weight (Kg)	138
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR

Engine manufacturer

Honda
