



GENSET MG 10 S-KL - SINGLE-PHASE/THREE-PHASE GENERATOR 10 KVA

Reference: MG 10 S-KL

GENSET MG10S-KL Single Phase/Three Phase Generator 10KVA

GENSET MG10S-KL is a singlephase/threephase 10KVA generator with Kubota Stage V engine powered by diesel at 1500 rpm, compact and easy to use, mounted on a fixed base. This GENSET MG10S-KL generator set is in the open version and is easy to handle and transport, despite its weight, thanks to the base with pivoting feet.

The GENSET MG10S-KL generator is composed of a synchronous alternator. The GENSET MG10S-KL generator set is equipped with an electric start with battery with a low fuel consumption in fact it consumes only 2 liters/hour.

This genset is perfect for outdoor use such as construction. The GENSET MG10S-KL generator set is part of the Industrial range and is characterized by versatility in installation in urban environments such as stores or shopping malls, for the telecommunications environment, for military applications and much more.

This generator set is perfect for outdoor use such as construction sites.

The GENSET MG10S-KL comes complete with:

- Automatic engine stop device with warning lights for:
 - battery charge failure
 - high water temperature
 - low fuel level
 - low oil pressure
- 1 threephase socket CEE 400V - 16A
- 1 singlephase socket CEE 230V - 16A
- 12 V battery
- Power output protections
- Differential switch
- Voltmeter
- Hour meter
- Emergency stop button
- Forks passage

Technical features GENSET MG10S-KL:

Phase Type: SinglePhase/ThreePhase
Maximum SinglePhase Power: 3.3 KVA / 2.64 KW
Maximum ThreePhase Power: 10 KVA / 8 KW
Three-Phase Continuous Power: 9 KVA / 7.2 KW
VAC Voltage: 230 / 400 V
Frequency (Hz): 50

Starting Frame: Electric
 Motor: Kubota D1105
 Emission Standard: Stage V
 RPM: 1500
 Power supply: Diesel
 Fuel tank capacity: 40 l
 Consumption @ 75 % load: 2 l/h
 Autonomy @ 75 % load: 20 h
 Sound pressure: 95 dB(A)
 Length: 1357 mm
 Width: 707 mm
 Height: 942 mm
 Net weight: 350 kg

If you're looking for a product like the GENSET MG10S-KL then you can browse the full range of [generator](#) of GENSET or other kind of products on our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	2.64
Maximum power single phase (KVA)	3.3
Maximum power three phase (KW)	8
Continuous power three phase (KW)	7.2
Maximum power three phase (KVA)	10
Continuous power three phase (KVA)	9
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A CEE - 1 x 230V 16A CEE
Engine	Kubota D1105
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	1123
Number cylinders	3
Cooling	Water
Alternator	Synchronous
Protection degree	IP23

Motor insulation class	H
Fuel tank capacity (L)	40
Consumption (L/h)	2
Running time (h)	20
Acoustic power	95 dB(A)
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	1357
Width (mm)	707
Height (mm)	942
Dry weight (Kg)	350
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	No
Engine manufacturer	Kubota