



GENSET MG 10000 S-KL - GENERATOR 10 KVA

Reference: MG10000 S-KL

GENSET MG 10000 S-KL SINGLE-PHASE POWER GENERATOR 10KVA STAGE V

GENSET MG 10000 S-KL Single-phase genset with Kubota D1105 STAGE V diesel-powered engine, capable of delivering a maximum power of 10KVA complete with AVR voltage regulator for autonomy up to about 24h.

The GENSET MG 10000 S-KL single-phase genset with autonomy of about 24 hours is compact and easy to use, equipped with an enclosure that lowers noise emissions and makes it super-silent.

The GENSET MG 10000 S-KL is a single-phase 10KVA diesel genset with electric start. This generator is also available in a version with AVR voltage regulator, with automatic panel and remote control.

Thanks to its compact dimensions and very low weight, the GENSET MMG 10000 S-KL is a light generator that is easy to transport. The GENSET MG 10000 S-KL also has a low fuel consumption: only 2 Lt/h at 75% load for an autonomy of up to approx. 24 h. The GENSET MG 10000 S-KL generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work requiring an autonomy of about 24h: from small hobby work to large construction sites.

The GENSET MG 10000 S-KL generator set includes:

- Automatic engine stop device with warning lights for:
 - battery charge failure
 - high water temperature
 - low fuel level
 - low oil pressure
- 1 single-phase CEE 230V - 32A outlet
- 1 single-phase 230V withdrawal
- 12 V battery
- Power output protections
- Differential switch
- Voltmeter
- Hour meter
- Emergency stop button
- Fork pass

TECHNICAL FEATURES GENSET MG 10000 S-KL

Phase Type: Single-Phase
Maximum Single-Phase Power: 10 KVA / 8 KW
Continuous Single-Phase Power: 9 KVA / 7.2 KW
VAC Voltage: 230 V
Frequency (Hz): 50

Starting Frame: Electric
Engine: Kubota D1105
Emissions Standard: STAGE V
RPM: 1500
Power supply: Diesel
Fuel tank capacity: 40 l
Consumption @ 75 % load: 2 l/h
Autonomy @ 75 % load: 20 h
Acoustic pressure: 95 dB(A)
Length: 1357 mm
Width: 707 mm
Height: 942 mm
Net weight: 350 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	8
Continuous power single phase (KW)	7.2
Maximum power single phase (KVA)	10
Continuous power single phase (KVA)	9
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 32A
Engine	Kubota D1105
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	1123
Number cylinders	3
Cooling	Water
Alternator	Synchronous
Protection degree	IP23
Motor insulation class	H
Fuel tank capacity (L)	40

Consumption (L/h)	2
Running time (h)	20
Acoustic power	95 dB(A)
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	1357
Width (mm)	707
Height (mm)	942
Dry weight (Kg)	350
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Capacitor
Engine manufacturer	Kubota