



MASE IS 34 T MARINE GENERATOR THREE-PHASE 36.2KVA

Reference: 002079

MASE IS 34 T THREE PHASE MARINE GENERATOR 36.2KVA

MASE IS34T marine generator Three-phase with Yanmar 4TNV98 engine with diesel power supply at 1500 rpm capable of delivering a power of 36.2KVA.

The MASE IS34T marine generator is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS34T is built with a Yanmar diesel-powered engine and synchronous alternator, self-excited with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS34T.

The soundproof cabin of the MASE IS34T consists of a load-bearing structure in aluminum profile that supports panels in marine aluminum painted type 5754 extremely light and very high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance easier even with the genset installed in narrow spaces.

Technical Features:

Phase Type: Three Phase
Continuous Use Power: 33.7KVA
Maximum Power: 36. 2KVA
Fuel: Diesel
Voltage: 400 V
Frequency: 50 Hz
Engine: Yanmar 4TNV98, 4 Stroke
Length: 1225 mm
Width: 630 mm
Height: 830 mm
Weight: 625 Kg

If you are looking for another generator as the MASE IS34T then you can see the entire catalog of [marine generator sets](#).

Images and technical data are not binding.

Phase	Three phase
Maximum power three phase (KW)	29
Continuous power three phase (KW)	27
Maximum power three phase (KVA)	36.2
Continuous power three phase (KVA)	33.7
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Yanmar 3TNV98, 4 stroke
Engine rpm (rpm)	1500
Speed governor	Centrifugal, mechanical
Engine capacity (cm ³)	3319
Number cylinders	4
Oil capacity (L)	10.5
Cooling	Air / water (Intercooler W/A)
Inyección	Direct
Alternator	Synchronous, self-excited
Poles	4
Compression ratio	18 : 1
Lubrication	Forced
Consumption (L/h)	10.8 at 100% of the load
Acoustic pressure	54 dB(A) at 7 m
Length (mm)	1225
Width (mm)	630
Height (mm)	830
Dry weight (Kg)	625
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	AVR
Engine manufacturer	Yanmar