



MASE EA 80 GH GENERATOR 7KVA SINGLE PHASE STAGE V

Reference: 001948

MASE EA 80 GH GENERATOR 7KVA SINGLE PHASE STAGE V

MASE EA 80 GH is a single-phase generator equipped with a Honda GX390 engine powered by gasoline, capable of delivering a maximum power of 7 KVA.

The MASE EA 80 GH single-phase generator provides reliable power for home, work and leisure environments, safely powering home appliances and other electronic devices.

The generator is as easy to install and operate as it is to start and stop thanks to clear, intuitive controls. MASE EA 80 GH is equipped with a Honda GX390 gasoline engine. They are very reliable engines that provide efficient combustion and **low fuel consumption**. The engines with which the generators are equipped are also equipped with a protection system that causes the engine to stop if the oil level is too low.

MASE EA 80 GH is a stationary use machine, before commissioning, you must first secure the generator firmly to the ground. The MASE EA 80 GH are equipped with **6.5litre** tank with a large cap that is convenient to unscrew even with work gloves

MASE EA 80 GH has an all-steel structure and a large metal tank. The generator guarantees an efficient and silent operation thanks to the Honda GX390 engine which allows to deliver a maximum power of 7 KVA.

The generator set is composed of:

- 1 single-phase socket CEE 32 A, 230 V - 50 Hz protected by a thermal switch;
- 1 single-phase socket CEE 16 A, 230 V - 50 Hz protected by a thermal switch;
- Battery charger outlet 12 Vdc protected by a fuse

On express request of the customer it is possible the additional supply of the transport trolley for the MASE EA 80 GH, the increased tank of 25 l and the AVR voltage regulator.

TECHNICAL CHARACTERISTICS MASE EA 80 GH

Maximum Single-Phase Power: 7 KVA
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Engine: Honda GX390 OHV
Engine Revs: 3000
Engine Displacement: 390 cm³
Cooling: Air
Starting: Manual
Tank Capacity: 6.5 l
Consumption: 2.9 Lt/h at 75% load

Acoustic power: 97 dB (72 dB at 7 m)
Protection class: IP 23
Length: 730 mm
Width: 480 mm
Height: 520 mm
Weight: 80 Kg

Are you looking for a power generator with different characteristics? [Here](#) you can find the full range of products MASE or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by supplier.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	5.6
Maximum power single phase (KVA)	7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 400V 16A CE - 2 x 230V 16A 2P+T CE
Engine	Honda GX390, 4 stroke, OHV
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Ignition	Recoil
Starting system	Manual
Engine capacity (cm ³)	390
Number cylinders	1
Cooling	Air
Alternator	Synchronous
Fuel tank capacity (L)	6.5
Consumption (L/h)	2.9 at 75% of the load
Running time (h)	2.24 at 75% of the load
Acoustic power	97 dB(A)
Acoustic pressure	72 dB(A) at 7 m
Length (mm)	730

Width (mm)	480
Height (mm)	520
Dry weight (Kg)	80
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Honda
