



MASE FX 50 H/A GENERATOR 4,5 KVA SINGLE PHASE STAGE V

Reference: 001896

MASE FX 50 H/A GENERATOR 4,5 KVA SINGLE PHASE STAGE V

MASE FX 50 H/A is a single-phase generator, equipped with a Honda GX 270 **StageV** Gasoline-powered engine, it delivers a maximum power of 5,4KW.

The MASE FX 50 H/A provides reliable power for home, business and leisure environments, safely powers home appliances and other electronic devices. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

The generator is easy to install and operate, just as simple are starting and stopping thanks to the clear and intuitive controls. MASE FX 50 H/A is equipped with a Honda GX 270 petrol engine. They are very reliable engines that guarantee efficient combustion and **reduced fuel consumption**, they are also equipped with a protection system that causes the engine to stop if the oil level is too low.

STAGEV EMISSIONS REGULATION

MASE FX 50 H/A is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

Technical characteristics of MASE FX 50 H/A

Type of phase: Single-phase
Continuous power: 4 KVA / 3.2 KW
Maximum power: 4.5 KVA / 3.6 KW
VAC voltage: 230 V
Frequency (Hz) : 50
Voltage regulator: Capacitor (AVR Optional)
Ignition panel: Electric
Engine: Honda GX 270
Emissions standard: Stage V
Revolutions per minute: 3000 rpm
Power supply: Gasoline
Sockets panel: 2 x CEE 16A 230V
Tank capacity: 5.3 l
Autonomy: 2.40 h at 75% of load
Consumption : 2.2 l / h at 75% load
Acoustic pressure: 74 dB (A) @ 7 m
Length: 725 mm
Width: 515 mm

Height: 585 mm
 Net weight: 78 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to MASE generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.6
Continuous power single phase (KW)	3.2
Maximum power single phase (KVA)	3.5
Continuous power single phase (KVA)	3.2
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V 16A CE
Engine	Honda GX270, 4 stroke
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	270
Number cylinders	1
Cooling	Air
Alternator	Synchronous
Fuel tank capacity (L)	6
Consumption (L/h)	2 at 75% of the load
Running time (h)	3 at 75% of the load
Acoustic power	99 dB(A)
Acoustic pressure	74 dB(A) at 7 m
Length (mm)	725
Width (mm)	515
Height (mm)	585
Dry weight (Kg)	78
Silenced	No
Super silenced	No

ATS Switch device

Optional ATS

Voltage regulator

Capacitor / AVR (optional)

Engine manufacturer

Honda
