

MASE MPV 16 BA

Reference: 007851



OUT OF PRODUCTION

Single-phase maximum power: 11 KW
Three-phase maximum power: 12.8 KW
Three-phase continuous use power: 12 KW
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Engine: Yanmar 3TNV88
Starting: Electric
Consumption: 2.5 Lt / h at 75% of the load
Length: 1750 mm
Width: 800 mm
Height: 900 mm
Weight: 600 Kg
Compound

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	11
Maximum power single phase (KVA)	11
Maximum power three phase (KW)	12.8
Continuous power three phase (KW)	12
Maximum power three phase (KVA)	16
Continuous power three phase (KVA)	15
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	2 x 230V 16A CE
Engine	Yanmar 3TNV88, 4 stroke

Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	1642
Number cylinders	3
Oil capacity (L)	6.7
Cooling	Water
Inyección	Direct
Alternator	Synchronous, self-excited
Poles	4
Lubrication	Forced
Fuel tank capacity (L)	50
Consumption (L/h)	2.5 at 75% of the load
Running time (h)	20 at 75% of the load
Acoustic power	94 dB(A)
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	1750
Height (mm)	900
Dry weight (Kg)	600
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	Compound
Engine manufacturer	Yanmar