

## MASE MPV 22 BA

Reference: 007852



### OUT OF PRODUCTION

Single-phase maximum power: 13.5 KW  
Three-phase maximum power: 17.6 KW  
Three-phase continuous use power: 16 KW  
Fuel: Diesel  
Voltage: 230 V / 400 V  
Frequency: 50 Hz  
Engine: Yanmar 3TNV88  
Starting: Electric  
Consumption: 2.5 Lt / h at 75% of the load  
Length: 1750 mm  
Width: 800 mm  
Height: 900 mm  
Weight: 600 Kg  
Compound

### Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	13.5
Maximum power single phase (KVA)	13.5
Maximum power three phase (KW)	17.6
Continuous power three phase (KW)	16
Maximum power three phase (KVA)	22
Continuous power three phase (KVA)	20
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	2 x 230V 16A CE
Engine	Yanmar 3TNV88, 4 stroke

Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	2190
Number cylinders	4
Oil capacity (L)	7.4
Cooling	Water
Inyección	Direct
Alternator	Synchronous self-excited, with brushes
Poles	4
Lubrication	Forced
Fuel tank capacity (L)	50
Consumption (L/h)	2.5 at 75% of the load
Running time (h)	20 at 75% of the load
Acoustic power	94 dB(A)
Length (mm)	1750
Height (mm)	900
Dry weight (Kg)	600
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	Compound
Engine manufacturer	Yanmar