

MASE MPV 33 BA

Reference: 007949



OUT OF PRODUCTION

Three-phase maximum power: 26.4 KW
Three-phase continuous use power: 24 KW
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Engine: Deutz F4M2011
Starting: Electric
Consumption: 5.26 Lt / h at 75% of the load
Length: 1877 mm
Width: 860 mm
Height: 1090 mm
Weight: 845 Kg
AVR

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	26.4
Continuous power three phase (KW)	24
Maximum power three phase (KVA)	33
Continuous power three phase (KVA)	30
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	2 x 230V 16A CE
Engine	Deutz F4M2011, 4 stroke
Engine rpm (rpm)	1500
Speed governor	Mechanical

Starting system	Electric
Engine capacity (cm ³)	3108
Number cylinders	4
Oil capacity (L)	10
Cooling	Oil
Inyección	Direct
Alternator	Synchronous self-excited, brushless
Poles	4
Lubrication	Forced
Fuel tank capacity (L)	50
Consumption (L/h)	5.26 at 75% of the load
Running time (h)	9.5 at 75% of the load
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	1877
Width (mm)	860
Height (mm)	1090
Dry weight (Kg)	845
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Deutz