



MASE IS 2.6

Reference: 008408

La linea di prodotti Mase marini è stata sviluppata per installazioni a bordo di imbarcazioni. I modelli IS (Intercooler System), generatori diesel dalle caratteristiche innovative, assicurano ai costruttori di imbarcazioni e agli utilizzatori finali estrema facilità d'installazione, alta efficienza, elevate prestazioni e silenziosità, garantendo al tempo stesso un bassissimo livello di impatto ambientale.

L'immagine è puramente indicativa

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	8.8
Maximum power single phase (KVA)	11
Maximum power three phase (KW)	26.4
Continuous power three phase (KW)	24
Maximum power three phase (KVA)	33
Continuous power three phase (KVA)	30
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	2 x 230V 16A CE
Engine rpm (rpm)	1500
Alternator	Linz PRO18SC/4, synchronous, brushless
Poles	4
PTO speed (round/min)	440

Transmission ratio	1 : 3.5
Length (mm)	1235
Width (mm)	945
Height (mm)	809
Dry weight (Kg)	300
Inverter	No
AVR	No
Compound	No
Silenced	No
Super silenced	No