



## MASE MPL 16 I-SY

Reference: 009025 - AVR

La linea di prodotti Mase marini è stata sviluppata per installazioni a bordo di imbarcazioni. I modelli IS ( Intercooler System), generatori diesel dalle caratteristiche innovative, assicurano ai costruttori di imbarcazioni e agli utilizzatori finali estrema facilità d'installazione, alta efficienza, elevate prestazioni e silenziosità, garantendo al tempo stesso un bassissimo livello di impatto ambientale.

L'immagine è puramente indicativa

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	10.48
Continuous power three phase (KW)	10
Maximum power three phase (KVA)	13.1
Continuous power three phase (KVA)	12.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	2 x 230V 16A CE
Engine	Deutz F2M2011, naturally aspirated
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	1554
Number cylinders	2

Cooling	Oil
Alternator	Synchronous
Fuel tank capacity (L)	65
Consumption (L/h)	2.6 at 75% of the load
Running time (h)	25 at 75% of the load
Acoustic power	92 dB(A)
Acoustic pressure	67 dB(A) at 7 m
Length (mm)	1950
Width (mm)	900
Height (mm)	1125
Dry weight (Kg)	650
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	Compound / AVR (optional)
Engine manufacturer	Deutz