



MASE IS 2.6

Reference: MPL 330 S-I

La linea di prodotti Mase marini è stata sviluppata per installazioni a bordo di imbarcazioni. I modelli IS (Intercooler System), generatori diesel dalle caratteristiche innovative, assicurano ai costruttori di imbarcazioni e agli utilizzatori finali estrema facilità d'installazione, alta efficienza, elevate prestazioni e silenziosità, garantendo al tempo stesso un bassissimo livello di impatto ambientale.

L'immagine è puramente indicativa

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	88
Maximum power single phase (KVA)	110
Maximum power three phase (KW)	264
Continuous power three phase (KW)	240
Maximum power three phase (KVA)	330
Continuous power three phase (KVA)	300
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	FPT (IVECO) CURSOR 10TE1D turbo
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	10300

Number cylinders	6
Cooling	Water
Alternator	Synchronous
Fuel tank capacity (L)	420
Consumption (L/h)	53.7 at 75% of the load
Running time (h)	7.82 at 75% of the load
Acoustic power	97 dB(A)
Acoustic pressure	72 dB(A) at 7 m
Length (mm)	3865
Width (mm)	1584
Height (mm)	2171
Dry weight (Kg)	3550
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	No
Engine manufacturer	FPT Iveco