



TECNOGEN LD7500TELX Generator Set Three-Phase 7.3KVA

Reference: LD 7500 TELX - COMP

TECNOGEN LD7500TELX GENERATOR SET THREE-PHASE 7.3KVA

TECNOGEN LD7500TELX Generator Set Three-Phase 7.3KVA with Kohler engine running at 3000 RPM and powered by diesel. The TECNOGEN LD7500TELX Generator is easy to use, compact, handy, and easy to maintain. It is equipped with an electric start. This TECNOGEN LD7500TELX Three-Phase 7.3KVA generator is perfect for both hobby and professional use, thanks to its reliable Kohler diesel engine and high-quality components.

Main Features of the TECNOGEN LD7500TELX Generator Set Three-Phase 7.3KVA:

Maximum three-phase power: 5.8 KW
Maximum three-phase power: 7.3 KVA
Fuel: Diesel
Voltage: 400 - 230 V
Engine: Kohler 15LD440
Start: Electric
Length: 750 mm
Width: 560 mm
Height: 620 mm
Weight: 121 Kg

Why buy a TECNOGEN LD7500TELX Generator Set Three-Phase 7.3KVA?

First of all, it solves power outage problems in various environments, from homes to businesses. The TECNOGEN LD7500TELX generator is also used to provide electricity on construction sites and for hobby applications.

The TECNOGEN LD7500TELX Three-Phase 7.3KVA can be equipped with lifting hooks, making it easy to move using an overhead crane or a small hoist.

The complete TECNOGEN range:

TECNOGEN generators are available in both single-phase and three-phase versions, with power outputs ranging from 2.3 to 21 KVA MAX, equipped with petrol or diesel engines, air-cooled, running at 3000 RPM, with electric and/or manual recoil start. Compact, simplified, and economical, TECNOGEN generators offer an excellent price/performance/size/weight ratio. This generator is lightweight and easy to transport, making it suitable for various applications.

Looking for a different model of the TECNOGEN LD7500TELX Generator Set Three-Phase 7.3KVA? Visit the dedicated section for [power generators](#).

Images and technical data are for reference only and subject to possible manufacturer revisions.

Technical Sheet

Phase

Single phase / Three phase

| | |
|------------------------------------|---------------------------|
| Maximum power single phase (KW) | 3.1 |
| Maximum power single phase (KVA) | 3.8 |
| Maximum power three phase (KW) | 5.9 |
| Maximum power three phase (KVA) | 7.3 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Engine | Kohler 15LD440 |
| Engine rpm (rpm) | 3000 |
| Starting system | Elettrico |
| Engine capacity (cm ³) | 442 |
| Number cylinders | 1 |
| Cooling | Air |
| Fuel tank capacity (L) | 20 |
| Consumption (L/h) | 1.6 al 75% del carico |
| Running time (h) | 12.5 |
| Length (mm) | 750 |
| Width (mm) | 560 |
| Height (mm) | 620 |
| Dry weight (Kg) | 121 |
| Silenced | No |
| Super silenced | No |
| ATS Switch device | Optional ATS |
| Voltage regulator | Compound / AVR (optional) |
| Engine manufacturer | Kohler |