



TECNOGEN LD7500TESX

Reference: LD 7500 TESX - COMP

TECNOGEN LD7500TESX 6.4 KW Generator Set

TECNOGEN LD7500TESX three-phase 6.4 KW generator set with a Kohler engine running at 3000 rpm powered by diesel. The TECNOGEN LD7500TESX generator set is easy to use and is compact, manageable, and easy to maintain. The TECNOGEN LD7500TESX generator set is equipped with an electric start. This generator set is perfect for both hobby and professional use, thanks to the reliable diesel-powered Kohler engine and all the high-quality components it is made of.

Why buy an LD7500TESX generator set?

First of all, they solve power outage problems during blackouts in various environments, from homes to businesses. The TECNOGEN LD7500TESX generator set is also used to provide electricity on construction sites and for hobby use. Professional generators are lightweight, easy to transport, compact and robust machines, simple to use and with low 1 operating costs. They also have an excellent quality/price ratio.

Lifting hooks can be installed on the TECNOGEN LD7500TESX generator set, which are very convenient for moving the generator with an overhead crane or a small crane.

Below are the main features:

Continuous Three-phase Power: 4.6 kW

Maximum Three-phase Power: 5.1 KW

Maximum Three-phase Power: 6.4 KVA

Fuel: Diesel

Voltage: 400V

Engine: Kohler

Start: Electric

Length: 750 mm

Width: 560 mm

Height: 620 mm

Weight: 170 Kg

Are you looking for a different model of generator or generator set? Visit the section dedicated to [land generator sets](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	5.1

Maximum power three phase (KVA)	6.4
Fuel	Diesel
Frequency (Hz)	50 / 60
Voltage (V)	400
Engine	Kohler
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm ³)	442
Number cylinders	1
Cooling	Air
Fuel tank capacity (L)	20
Consumption (L/h)	1.6 al 75% del carico
Running time (h)	13.3
Acoustic power	95 dB(A)
Length (mm)	750
Width (mm)	560
Height (mm)	620
Dry weight (Kg)	170
Silenced	Yes
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	No
Continuous power [kW]	4.6