



PRAMAC TG25/3 IP23 Cardan generator Single-phase-Three-phase 25kVA

Reference: MB25000TZ00

PRAMAC TG25/3 IP23 Cardan generator Single/Three-Phase 25 kVA

PRAMAC TG25/3 IP23 Cardan generator, 12 kVA single-phase and 25 kVA three-phase, with tractor connection at 3000 rpm. The PRAMAC TG25/3 IP23 Cardan generator has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC TG25/3 IP23 PTO generator features a compound voltage regulator. The compound regulator stabilizes the voltage and prevents damage to connected devices. The TG25/3 IP23 Cardan generator is highly reliable as it has been built and designed using high-quality materials.

Easy to transport, install, and position thanks to its compact size, this model is ideal for mounting on a tractor unit. The PRAMAC TG25/3 IP23 Cardan generator requires a tractor power of 44 kW / 60 HP and a PTO speed of 435 rpm.

Technical specifications of the PRAMAC TG25/3 IP23 Cardan generator Single-Three-Phase:

Continuous power single-phase: 12 kW
Continuous power three-phase: 20 kW
Voltage: 230 V / 400 V
Frequency: 50 Hz
Generator speed: 435 rpm
Required tractor power: 44 kW / 60 HP
Length: 958 mm
Width: 645 mm
Height: 1003 mm
Weight: 154 kg
Compound

Outlets:

N.1 SCHUKO 230V 16A IP54
N.1 2P+T CEE 230V 32A IP44
N.1 3P+N+T CEE 400V 32A IP44

The PRAMAC TG25/3 IP23 Cardan generator is a professional tractor-driven unit developed by Pramac, making it one of the best choices compared to its competitors. The PRAMAC TG25/3 IP23 Cardan generator features a robust structure with a protective tubular frame. This series is the ideal solution for agricultural applications, enabling access to remote areas even under adverse weather conditions.

The TG25/3 IP23 Cardan generator is equipped with thermal-magnetic protection, residual current protection, voltmeter, and frequency meter.

If you are looking for a Cardan generator like the PRAMAC TG25/3 IP23 single/three-phase tractor-driven unit, we recommend browsing our catalog of [Cardan generators](#) to find the one that best suits your needs.

Phase	Single phase / Three phase
Continuous power single phase (KW)	9.6
Continuous power single phase (KVA)	12
Continuous power three phase (KW)	20
Continuous power three phase (KVA)	25
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 32A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine rpm (rpm)	3000
PTO speed (round/min)	435
Required tractor power	44 KW / 60 HP