



PRAMAC TG30/15 IP23 Cardan generator Single-phase-Three-phase 30KVA AVR

Reference: MB30000TZ01

PRAMAC TG30/15 IP23 Cardan Generator Single/Three-Phase 30 kVA AVR

PRAMAC TG30/15 IP23 cardan generator, 12 kVA single-phase and 30 kVA three-phase, with tractor connection at 1500 rpm. The PRAMAC TG30/15 IP23 cardan generator has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC TG30/15 IP23 cardan generator has an AVR voltage regulator. The AVR regulator stabilizes the voltage and prevents damage to connected devices. The TG30/15 IP23 AVR cardan generator is highly reliable as it has been built and designed using high-quality materials.

Easy to transport, install, and position thanks to its compact size, this model is ideal for mounting on a tractor unit. The PRAMAC TG30/15 IP23 cardan generator requires a tractor power of 51 kW / 70 HP and a cardan shaft speed of 430 rpm.

Technical specifications of the PRAMAC TG30/15 IP23 AVR Cardan Generator Single/Three-Phase:

Continuous power single-phase: 12 kW

Continuous power three-phase: 24 kW

Voltage: 230 V / 400 V

Frequency: 50 Hz

Cardan shaft speed: 430 rpm

Required tractor power: 51 kW / 70 HP

Length: 958 mm

Width: 645 mm

Height: 1003 mm

Weight: 213 kg

AVR

Sockets:

N.1 SCHUKO 230V 16A IP54

N.1 2P+T CEE 230V 32A IP44

N.1 3P+N+T CEE 400V 63A

The PRAMAC TG30/15 IP23 cardan generator is a professional tractor-driven unit developed by Pramac, making it one of the best choices compared to its competitors. The PRAMAC TG30/15 IP23 cardan generator features a robust structure with a protective tubular frame. This series is the ideal solution for agricultural applications, also allowing access to hard-to-reach areas even under adverse weather conditions.

The TG30/15 IP23 cardan generator is equipped with thermal-magnetic protection, residual current protection, voltmeter, and frequency meter.

If you are looking for a cardan generator like the PRAMAC TG30/15 IP23 AVR single/three-phase tractor-driven unit, we recommend browsing our [catalog of cardan generators](#) to find the one that best suits your needs.

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	9.6
Continuous power single phase (KVA)	12
Continuous power three phase (KW)	24
Continuous power three phase (KVA)	30
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 63A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine rpm (rpm)	1500
PTO speed (round/min)	430
Required tractor power	51 KW / 70 HP