



VTE PAGURO 18000 Marine Generator Supersilenced 18 kVA 50 Hz

Reference: AP18023050S0

PAGURO18000/50 Hz VTE super-silenced 14 KVA marine generator set

PAGURO18000/50Hz VTE single-phase 18 KVA marine genset VTE PAGURO18000/50Hz, with Lombardini engine powered by diesel at 3000 rpm and water-cooled with stainless steel water/air heat exchanger.

All parts in contact with seawater are made of 316 L stainless steel.

Thanks to the double anti-vibration system, vibrations are reduced to a minimum, making the VTE PAGURO18000/50 Hz marine genset supersilenced and among the lowest noise emission marine generators in its category.

The compact and space-saving VTE PAGURO18000/50 Hz marine genset is suitable for use on small boats, ready to give you all the power you need in peace.

This generator is the right solution for excellent reliability, Paguro18000/50 Hz means power.

Technical characteristics:

Fuel: Diesel
Engine speed (rpm): 3000
Phase type: Single-phase
Single-phase continuous power (KVA): 18
Frequency (Hz): 50
Voltage (V): 230
Engine: Lombardini LDW 1404
Starter: Electric
Silenced: Supersilenced 54 dB(A)
Cooling: Fresh water with heat exchanger
Dry weight (kg): 230
Length (mm): 970
Width (mm): 580
Height (mm): 650

Engine

The PAGURO18000/50 Hz Lombardini diesel-powered engine makes the VTE PAGURO18000/50 Hz marine genset efficient and reliable.

Designed with a stainless steel water/air heat exchanger.

Alternator

The alternator of this genset is synchronous, brushless and with class H insulation. The genset's capacitor regulation makes the PAGURO18000/50 Hz marine genset excellent for powering sensitive electronic devices that fear voltage and current surges. It is also water-cooled via an AISI 316 L stainless steel heat exchanger.

Included with the alternator is the battery charger for the dedicated 12 V / 8 A starter battery.

Soundproofing capsule and double anti-vibration system

The reinforced fibreglass capsule with composite layering and the high-density soundproofing material coating make this generator set one of the most silent compared to its competitors.

The capsule allows installation even in cramped spaces, thanks to its composition: two upper parts and one lower part.

Finally, the dual anti-vibration system, with 4 soft inner mounts and 4 semi-elastic outer mounts, makes the PAGURO18000/50 Hz stable even in less calm waters and silenced, so you can enjoy your navigation without further worries.

If you are looking for a product similar to the PAGURO18000/50 Hz genset or with different characteristics, you can consult our entire catalogue of marine gensets [CLICK HERE](#).

Non-binding images and technical data.

Technical Sheet

Phase	Single phase
Continuous power single phase (KW)	16
Continuous power single phase (KVA)	18
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Engine	Lombardini LDW1404
Engine rpm (rpm)	3000
Starting system	Elettrico
Number cylinders	4
Cooling	Fresh water with heat exchanger
Alternator	Synchronous, brushless
Consumption (L/h)	0.35
Acoustic pressure	54 dB(A)
Length (mm)	970
Width (mm)	580
Height (mm)	650
Dry weight (Kg)	230
Silenced	Yes
Super silenced	Yes
Product type	Generator
Engine manufacturer	LOMBARDINI