



TECNOGEN SH180E

Reference: SH180E

TECNOGEN SH180E MOTORWELDING 4,5KVA

TECNOGEN SH180E features a rugged frame to protect a powerful HONDA GX270 motor capable of delivering 4.5KVA single-phase power with a maximum load consumption of 2.4 L/h.

TECNOGEN SH180E is with electric start with 12V battery supplied with acid or manual with self-winding, with control panel QM115 composed of singlephase CEE socket 2P+T 16A, thermal protection, singlephase Schuko socket 2P+T 16A.

TECHNICAL FEATURES TECNOGEN SH180E

Soldering at 60%: 170
Maximum single-phase power: 4.5 KVA
Fuel: Gasoline
Voltage: 230V
Engine: Honda GX270
Boosting: Electric
Length: 780 mm
Width: 520 mm
Height: 560 mm
Weight: 80 Kg

Are you looking for a motorwelding with different technical characteristics? [Here](#) you can find the full range of TECNOGEN and other specialized brands.

The images are purely indicative.

Technical Sheet

Phase	Single phase
Maximum power single phase (KVA)	4.5
Fuel	Gasoline
Frequency (Hz)	50

Voltage (V)	230
Engine	HONDA GC160
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	160
Number cylinders	1
Cooling	Air
Welding current (A)	180 al 35% - 170 al 60%
Fuel tank capacity (L)	2
Consumption (L/h)	0,8 al 75% del carico
Running time (h)	2,5
Acoustic power	95 dB(A)
Length (mm)	78
Width (mm)	52
Height (mm)	56
Dry weight (Kg)	27
Inverter	No
AVR	No
Compound	No
Silenced	Yes
Super silenced	No