



## TECNOGEN LD22000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Reference: LD22000TSS/A

### TECNOGEN LD22000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Super-silenced diesel generator sets with electric start, air-cooled, 3000 rpm, available in both single-phase and three-phase versions, with powers from 6.3 to 21 kVA MAX. Extremely small in size, the carpentry of this series boast a particular configuration that facilitates routine maintenance operations. The excellent performance / size ratio and the high level of soundproofing make these generators the ideal solution for limited spaces in which it is necessary to operate with the utmost silence (vans set up for road maintenance, mobile workshops, etc.). Easy and versatile to position, they are also suitable for installations with automatic intervention electrical panel, in full compliance with current regulations.

The image is purely indicative.

#### Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	5.6
Maximum power single phase (KVA)	7
Maximum power three phase (KW)	16.8
Maximum power three phase (KVA)	21
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	HONDA GC160
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	1248
Number cylinders	2
Cooling	Air
Fuel tank capacity (L)	48

Consumption (L/h)	4.9 at 75% of the load
Running time (h)	9.7 at 75% of the load
Acoustic power	96 dB(A)
Length (mm)	1450
Width (mm)	800
Height (mm)	1060
Dry weight (Kg)	400
Silenced	No
Super silenced	Yes
ATS Switch device	ATS Included
Voltage regulator	Compound
Engine manufacturer	Lombardini