



TECNOGEN LW16000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Reference: LW16000TSS/A

TECNOGEN LW16000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Electric start diesel generators, water-cooled, 3000 rpm, available in both single-phase and three-phase versions, with powers from 11.7 to 34.7 kVA MAX. Sturdy and reliable, they are suitable to operate for long periods despite the high rotation rate. The set-up relative to the base-mounted versions includes a built-in fuel tank with a capacity of 52 l, a metal grille placed to protect the radiator and a professional electrical panel, entirely made of ABS with a high degree of protection, equipped with instruments that respect the strictest safety standards. The silenced models are also equipped with a soundproofed canopy in hot-dip galvanized steel. The generators of the W 3000 series are the ideal choice for applications with automatic intervention panel or for use in the mechanical / industrial field.

The image is purely indicative.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	4.7
Maximum power single phase (KVA)	5.8
Maximum power three phase (KW)	14
Maximum power three phase (KVA)	17.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	HONDA GC160
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	1028
Number cylinders	3
Cooling	Water
Fuel tank capacity (L)	54

Consumption (L/h)	3.5
Running time (h)	15.4
Acoustic power	94 dB(A)
Length (mm)	1750
Width (mm)	770
Height (mm)	1070
Dry weight (Kg)	405
Silenced	No
Super silenced	Yes
ATS Switch device	ATS Included
Voltage regulator	Compound / AVR (optional)
Engine manufacturer	Lombardini