

HONDA Outboard BF 150 SHU 43 cm Shaft With Tiller 11.2 kW 15 Hp 350cm³



Reference: BF 15DK2 SHU

HONDA BF15DK2 SHU outboard shaft 43 cm Bar Guide

HONDA BF15DK2 SHU 15 or 20 horsepower outboards that are incredibly practical and portable, featuring well-placed retractable handles. They are perfect for any boat that needs power in a small size.

The 4-stroke engine stays quiet both when starting and when increasing its power; they're so quiet you can take them to their full power without having to raise your voice to speak. Honda's exclusive vibration-absorbing rubber mounting system gives a great impression of smoothness.

These Honda 350 cm³ 4-stroke engines are easy to start, thanks to the decompression system and PGM-IG programmed ignition. This ignition system precisely delivers the right amount of air/fuel mixture to the twin cylinders. The engine, even when cold, is able to deliver all the power required.

HONDA BF15DK2 SHU have an automatic decompression system that makes starting easier. This makes the engine easier to start in the initial pull in the case of manual starting and places much less strain on the battery in the case of electric starting.

During forward motion, the propeller is driven normally through the water, as with all marine engines. In the reverse direction, however, Honda engines make all the difference. This unique reverse exhaust system directs bubbles out of the propeller so it can "grip" the water. The result is immediate response and very precise control.

The lightweight HONDA BF15DK2 SHU outboard rises easily in five steps. Both the manual start and electric start versions allow for raising and lowering, allowing you to adjust the boat's trim for maximum performance and fuel efficiency at all times. This also prevents damage to the propeller blades when the boat is close to rocks or shallow waters.

The HONDA BF15DK2 SHU engines have a reverse lever that allows you to shift gears with your fingertips. Everything is much easier to use and better positioned than other outboards even for left-handed people. Plus, the soft-grip, twist-lock throttle knob minimizes operating effort, increasing handling. You can throttle up and slow down as needed to navigate, or keep the control locked as cruise control.

HONDA BF15DK2 SHU outboards are available with rudder and remote control options. The remote control option displays engine warning lights, oil pressure and overheating. It also generates an audible signal to get your attention in case anything happens while you're focusing on other activities. It's unlikely, but if there's a problem, you'll have time to act.

First, the aluminum housing is anodized using Honda's patented "double seal" process. Then a layer of epoxy primer is applied before the silver gloss paint. As additional UV protection, a clear resin is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

TECHNICAL CHARACTERISTICS HONDA BF15DK2 SHU

Net Power (kW): 11.2
 Net Power (Hp): 15
 Displacement: 350 cm³
 Shaft length: Long
 Dry weight (Kg): 46.5
 Starter: Electric / Manual
 Ignition system: Electronic PGM-IG
 Control type: Bar
 Setup and engine lifting: Manual / Manual 5 positions
 Transom height (mm): 433
 Length (mm): 650
 Width (mm): 350
 Height (mm): 1110
 Bore x stroke: 59 x 64 mm
 Engine Brand: Honda
 Engine Type: OHV, 4 stroke
 Number of cylinders: 2
 Speed at full throttle (rpm): 4500-5500
 Cooling system: Water
 Battery charge capacity (A): 6

Are you looking for an outboard with different technical characteristics? [Here](#) you can find the entire Honda range or other brands specializing in the field.

Images are indicative only.

Technical Sheet

Fuel	Gasoline
Engine	OHV, 4 stroke
Ignition	Electronic PGM-IG
Starting system	Manual / Electric
Engine capacity (cm ³)	350
Number cylinders	2
Cooling	Water (with thermostat)
Bore x stroke (mm)	
Reduction ratio	2.08
Rpm at full throttle (rpm)	4500 - 5500
Appearance and engine lifting	Manual / Manual 5 position
Transom height (mm)	
Net power (kW)	
Fuel tank capacity (L)	12
Length (mm)	650
Width (mm)	
Height (mm)	1110
Dry weight (Kg)	

Shaft Length	S
Controls	Tiller
