



## PRAMAC E4500 SINGLE PHASE

Reference: PA322SY3000

### PRAMAC E4500 Single-phase Generator 3.5 KW

PRAMAC E4500 single-phase generator with 3.5 KW power and Yanmar engine at 3000 rpm in an open version. The PRAMAC E4500 generator is equipped with a manual recoil start with auto-rewind. The alternator of the PRAMAC E4500 generator is brushless with a capacitor voltage regulator. The Yanmar engine makes this generator **very reliable**, and its design uses high-quality materials.

Thanks to its very low weight and **compact dimensions**, it is convenient to transport wherever you need it most. The PRAMAC E4500 generator is suitable for outdoor use on small construction sites or for small outdoor hobby work.

#### Technical characteristics of the PRAMAC E4500 generator:

##### Maximum single-phase power: 3.5 KW

Continuous single-phase power: 3 KW  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Engine: Yanmar L70N Recoil  
Starting: Recoil start  
Consumption: 1.2 Lt/h at 100% load  
Length: 760 mm  
Width: 540 mm  
Height: 560 mm  
Weight: 54 Kg  
emissions: not emitted

#### CONTROL PANEL

##### Controls:

- Start - Stop control lever
- Decompression lever
- Ignition: Recoil auto-rewind
- Fuel tap

##### Outlets:

N.1 SCHUKO 230V 16A IP54  
 N.1 2P+T CEE 230V 16A IP44

The PRAMAC E4500 current generator is a diesel generator developed by Pramac to ensure a high level of quality and performance at an attractive price. The PRAMAC E4500 current generator is ideal for intensive applications, characterized by a robust structure with a supporting tubular frame that simplifies both its use and maintenance operations.

The E4500 current generator is the essential tool to meet professional applications.

If you are looking for a generator like the PRAMAC E4500 current generator, then we recommend browsing our catalog of [land generators](#) to find the one that best suits your needs.

Images and technical data are not binding. Always refer to the technical data sheet issued by the manufacturer. Manel service does not assume responsibility for any changes made by the manufacturer.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.5
Continuous power single phase (KW)	3
Maximum power single phase (KVA)	3.9
Continuous power single phase (KVA)	3.3
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Engine	Yanmar L70N Recoil, naturally aspirated
Engine rpm (rpm)	3000
Speed governor	Mechanical
Ignition	Recoil
Starting system	Pull starter
Engine capacity (cm <sup>3</sup> )	320
Oil capacity (L)	1.1
Cooling	Air
Alternator	Brushless
Poles	2
Fuel tank capacity (L)	3.5
Consumption (L/h)	0.9 at 75% of the load / 1.2 at 100% of the load
Running time (h)	3.8 at 75% of the load / 2.8 at 100% of the load
Length (mm)	760
Width (mm)	540

---

Height (mm)	560
Dry weight (Kg)	54
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Capacitor
Engine manufacturer	Yanmar

---