

PRAMAC GBW22P OPEN WITH MANUAL CONTROL PANEL (MCP)

Reference: SH200TPAL00 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	17.46
Continuous power three phase (KW)	15.42
Maximum power three phase (KVA)	21.82
Continuous power three phase (KVA)	19.78
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	PERKINS 404D-22G, naturally aspirated
Emissions Regulations	Stage 3A
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	2216
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	10.6
Cooling	Water
Fuel tank capacity (L)	51
Consumption (L/h)	4 at 75% of the load / 5.3 at 100% of the load
Running time (h)	12.8 at 75% of the load / 9.7 at 100% of the load

Length (mm)	1600
Width (mm)	870
Height (mm)	950
Dry weight (Kg)	425
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Compound
Engine manufacturer	Perkins
