

PRAMAC GBW45P APERTO CON QUADRO COMANDO MANUALE (MCP)

Reference: SH450TPAI00 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	38.4
Continuous power three phase (KW)	36.59
Maximum power three phase (KVA)	48
Continuous power three phase (KVA)	45.74
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Emissions Regulations	Stationary Use
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	3300
Number cylinders	3
Cylinders' position	In line
Oil capacity (L)	7.9
Cooling	Water
Alternator	Mecc Alte ECO/P32-3S/4, brushless
Poles	4
Fuel tank capacity (L)	51
Consumption (L/h)	8.2 at 75% of the load / 10.7 at 100% of the load

Running time (h)	6.2 at 75% of the load / 4.8 at 100% of the load
Length (mm)	2000
Width (mm)	920
Height (mm)	1100
Dry weight (Kg)	785
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Perkins