

PRAMAC GSL65D

Reference: SG610TDAU00 /



Compliance with Directive 2000/14/EC on environmental noise emissions and the high level of safety, which minimizes the danger of unauthorized use or accidental damage, make this series of generators suitable for all industrial and residential applications.

- DEUTZ diesel engines (prepared for BIODIESEL)
- ? Oil cooling with radiator
- ? MECCALTE electronic control alternators
- ? Galvanized casing with residential muffler
- ? Lifting hook and forklift base with trolleys
- ? Motor fluids and charged battery
- ? Oil extraction piping
- ? MCP cabinet with 4 service sockets (GSL65 optional)
- ? ETB terminal block power connection GSL65
- ? KPR Dispersed liquid collection basin (std ACP)

The images are purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	51.47
Continuous power three phase (KW)	48.76
Maximum power three phase (KVA)	64.34
Continuous power three phase (KVA)	60.95
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Emissions Regulations	Stationary Use
Speed governor	Mechanical
Starting system	Electric

Engine capacity (cm ³)	5650
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	13.5
Cooling	Air
Alternator	Mecc Alte ECO/P32-2L/4, brushless
Poles	4
Fuel tank capacity (L)	240
Consumption (L/h)	10.7 at 75% of the load / 14.7 at 100% of the load
Running time (h)	22.4 at 75% of the load / 16.3 at 100% of the load
Length (mm)	2200
Width (mm)	1000
Height (mm)	1620
Dry weight (Kg)	954
Inverter	No
AVR	Yes
Compound	No
Silenced	No
Super silenced	No