



NANNI QLS22T

Reference: QLS22T

NANNI QLS22T MARINE GENERATOR 17.7KW

NANNI QLS22T is a three-phase marine generator equipped with a Kubota 4-stroke engine with Diesel power supply capable of delivering a maximum power of 17.7KW.

The NANNI QLS22T is equipped with a Kubota base engine used for years in marine and industrial applications all over the world. Engine block in cast iron of tunnel type and gear distribution.

The NANNI QLS22T generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures. The cooling system allows the engine to run at an optimal temperature. In the case of closed loop heat exchanger cooling, the coolant is cooled by seawater passing through the exchanger.

NANNI QLS22T is complete with freshwater and saltwater exchanger. Also available with keel cooling system, also known as Keel Cooling. Accessible sea water pump with rubber impeller.

Instrument panel allows you to start and stop the generator, and provides you with important information about the generator set when it is running.

The alternator of the NANNI QLS22T provides 15.1 KW in continuous operation and can produce up to 19.7 KW. Protection level IP23 (protection level available on request).

NANNI QLS22T TECHNICAL FEATURES

Maximum three-phase power: 17.7 KW
Continuous three-phase power use: 15.1 KW
Fuel: Diesel
Voltage: 400 V
Frequency: 50 Hz
Engine: Kubota, 4-stroke
Start: Electric
Consumption: 4.8 Lt/h at full load
Length: 1167 mm
Width: 548 mm
Height: 692 mm
Weight: 360 Kg

Are you looking for a marine power generator with different technical features? [Here](#) you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	17.7
Continuous power three phase (KW)	15.1
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Kubota, 4 stroke
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	2197
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	7.5
Cooling	Water
Inyección	Indirect (E-TVCS)
Alternator	Electronic regulator
Bore x stroke (mm)	87 x 92.4
Consumption (L/h)	4.8 at 100% of the load
Length (mm)	1167
Width (mm)	548
Height (mm)	692
Dry weight (Kg)	360