



NANNI QLS32T

Reference: QLS32T

NANNI QLS32T MARINE GENERATOR 25.7KW

NANNI QLS32T is a three-phase marine generator equipped with a Kubota 4-stroke engine with Diesel power supply capable of delivering a maximum power of 25.7KW.

The NANNI QLS32T is equipped with a Kubota base engine used for many years in marine and industrial applications all over the world.

Cast iron engine block of tunnel type with gear distribution.

The NANNI QLS32T generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures.

The cooling system allows the engine to run at an optimal temperature. In the case of closed loop heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. In a keel cooling system (Keel Cooling), the heat from the engine is dissipated by passing the coolant through pipes embedded in the hull.

NANNI QLS32T comes complete with freshwater and saltwater exchanger. Also available with keel cooling system, also known as Keel Cooling. Accessible seawater pump with rubber impeller.

Instrument panel allows you to start and stop the generator, and provides you with important information about the generator set when it is running.

The alternator of the NANNI QLS32T provides 23.4 KW in continuous operation and can produce up to 25.7 KW. Protection level IP23 (protection level available on request).

NANNI QLS32T TECHNICAL SPECIFICATIONS

Maximum three-phase power: 25.7 KW
Continuous three-phase power use: 23.4 KW
Fuel: Diesel
Voltage: 400 V
Frequency: 50 Hz
Engine: Kubota, 4-stroke
Start: Electric
Consumption: 8.2 Lt/h at full load
Length: 1304 mm
Width: 636 mm
Height: 814 mm
Weight: 550 Kg

Are you looking for a marine power generator with different technical features? [Here](#) you can find brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	25.7
Continuous power three phase (KW)	23.4
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Kubota, 4 stroke
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	3318
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	13
Cooling	Water
Inyección	Indirect (E-TVCS)
Alternator	Electronic regulator
Bore x stroke (mm)	98 x 110
Consumption (L/h)	8.2 at 100% of the load
Length (mm)	1304
Width (mm)	636
Height (mm)	814
Dry weight (Kg)	550