



## HYUNDAI 35613 Submersible electric pump INOX 550 W Clear and dirty water

Reference: 35613

Submersible electric pump for the movement of infiltration water, irrigation of small gardens, emptying of cellars, garages and basements, drainage of small construction sites and wells of wastewater.

It can be used in fixed or mobile installations.

Equipped with integrated float that determines the start when there is a situation of excessive water level.

Specific for clear/dirty water.

Equipment

- Float
- Power cable 10 m
- Stainless steel pump body

The main body of the pump is entirely made of stainless steel resistant to oxidation with increased durability.

Images and technical data are not binding.

### Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Pump type	Submersible Pump
Fluid type	Dirty water
Maximum output capacity (Lt/min)	140
Power (W)	550
Main body material	Stainless steel
Float	Yes
Thermal protection	Yes
Maximum use depth (m)	7
Maximum height (m)	7.5
Maximum flow (m <sup>3</sup> /h)	8.5
IP classification	IPX8

---

Diameter feed pipe	G1-1/4"
Power cable length (m)	10
Package dimensions (mm)	220 x 160 x 330
Gross weight (Kg)	5.4
Outlet diameter thread type (mm/inches)	32 mm 1 1/4"

---