



## HYUNDAI 35611 Submersible Electric Pump 750 W

Reference: 35611

Submersible electric pump for the movement of infiltration water, irrigation of small gardens, emptying of cellars, garages and basements, drainage of small construction sites and wells of wastewater.

It can be used in fixed or mobile installations.

Equipped with integrated float that determines the start when there is a situation of excessive water level.

Specifically for fresh water.

The main body of the pump is made of shock-resistant resin resistant to the oxidation typical of pumps made of metal material, increasing its durability over time.

### EQUIPMENT

- Float
- Power cable 10 m

Images and technical data are not binding.

### Technical Sheet

|                                  |                        |
|----------------------------------|------------------------|
| Frequency (Hz)                   | 50                     |
| Voltage (V)                      | 230                    |
| Pump type                        | Submersible Pump       |
| Fluid type                       | Clean water            |
| Maximum output capacity (Lt/min) | 205                    |
| Power (W)                        | 750                    |
| Main body material               | Impact-resistant resin |
| Float                            | Yes                    |
| Thermal protection               | Yes                    |
| Maximum use depth (m)            | 7                      |
| Maximum height (m)               | 8.5                    |
| Maximum flow (m <sup>3</sup> /h) | 12.5                   |
| IP classification                | IPX8                   |

---

|   |                 |
|---|-----------------|
| Diameter feed pipe                      | G1-1/2"         |
| Power cable length (m)                  | 10              |
| Product dimensions (mm)                 | 158 x 165 x 327 |
| Package dimensions (mm)                 | 220 x 160 x 360 |
| Gross weight (Kg)                       | 5               |
| Outlet diameter thread type (mm/inches) | 40 mm - 1" 1/2  |

---