



## HYUNDAI 35612 Submersible electric pump 750 W Clear and Dirty Water

Reference: 35612

Submersible electric pump for the movement of infiltration water, irrigation of small gardens, emptying of cellars, garages and basements, drainage of small construction sites and wells of wastewater.

It can be used in fixed or mobile installations.

Equipped with integrated float that determines the start when there is a situation of excessive water level.

Specifically for clear/dark water.

The main body of the pump is made of shock-resistant resin resistant to the oxidation typical of pumps made of metal material, increasing its durability over time.

### EQUIPMENT

- Float
- Power cable 10 m

Images and technical data are not binding.

### Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Pump type	Submersible Pump
Fluid type	Dirty water
Maximum output capacity (Lt/min)	215
Power (W)	750
Main body material	Impact-resistant resin
Float	Yes
Thermal protection	Yes
Maximum use depth (m)	7
Maximum height (m)	8
Maximum flow (m <sup>3</sup> /h)	13
IP classification	IPX8

---

Diameter feed pipe	G1-1/2"
Power cable length (m)	10
Product dimensions (mm)	158 x 165 x 456
Package dimensions (mm)	220 x 170 x 485
Gross weight (Kg)	5.7
Outlet diameter thread type (mm/inches)	40 mm - 1" 1/2

---